

	Type	L #	Hits	Search Text	DBs
1	IS&R	L1	4261	(359/819,198,254,811,815,820,826,827,871).CCLS.	US-PGPUB; USPAT; USOCR
2	BRS	L2	294	1 and @pd>"20040601"	US-PGPUB; USPAT
3	BRS	L3	6	2 and (silicon\$6 with aluminum\$6)	US-PGPUB; USPAT
4	BRS	L4	13	2 and (silicon\$6 same aluminum\$6)	US-PGPUB; USPAT
5	BRS	L5	262	2 and ((optic\$6 or lens\$2 or prism\$6 or mirror\$4) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or cas\$5 or clamp\$4))	US-PGPUB; USPAT
6	BRS	L6	19	5 and (silicon\$6 and aluminum\$6)	US-PGPUB; USPAT
7	BRS	L7	2	2 and ((silicon\$6 and aluminum\$6) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or cas\$5 or clamp\$4))	US-PGPUB; USPAT

	Type	Hits	Search Text	DBs
1	BRS	1249 55	silicon\$6 with aluminum\$6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
2	BRS	3010 25	silicon\$6 and aluminum\$6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
3	BRS	1160 9	S1 and @pd>"20040601"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
4	BRS	2838 9	S2 and @pd>"20040601"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
5	BRS	1960	S3 and ((optic\$4 or lens\$2 or plate\$1 or prism\$6 or mirror\$4) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
6	BRS	5753	S4 and ((optic\$4 or lens\$2 or plate\$1 or prism\$6 or mirror\$4) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
7	BRS	324	S6 and ((silicon and aluminum) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
8	BRS	206	S5 and ((silicon and aluminum) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
9	BRS	151	S5 and ((silicon with aluminum) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB

	Type	Hits	Search Text	DBs
10	BRS	109	S5 and ((silicon near4 aluminum) with (hold\$4 or clamp\$5 or mount\$4 or hous\$4 or barrel\$4 or case or casing\$2))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB